


| REVISIONS | | | | |
|-----------|-----|-------------|------|----------|
| ZONE | LTR | DESCRIPTION | DATE | APPROVED |
| | | | | |
| | | | | |



Isometric view (1:2)

NOTE

- MODEL No : SDP-2530FGT
- OPERATING PRESSURE : 15~250 Kg/cm²
- OPERATING TEMPERATURE : 0~60 °C
- EFFECTIVE AREA(Cm²) : PUSH=4.91 , PULL=2.36
- PISTON DIAMETER : $\phi 25.0$
- ROD DIAMETER : $\phi 18.0$

| DET.NO | NAME | Q'TY | MAT'L | FINAL SIZES & PART No | REMARK |
|----------------------------|------|---------------|-------|-----------------------|---|
| UNLESS OTHERWISE SPECIFIED | | SIGNATURES | | MO-DA-YR | |
| DIMENSIONS ARE IN MM | | DRAWN | | | |
| ALL SURFACES 6.3S | | CHECKED | | | |
| TOLERANCES | | APPROVED | | | |
| ANGLE | | | | | |
| X. ± | | | | | |
| .X ± 0.15 | | | | | |
| .XX ± | | | | | |
| FINISH | | WORK ORDER NO | | REF DWG NO. | DWG NO |
| HEAT TREAT | | | | --- | SDx-2522FGT |
| | | | | SCALE | TOOL <input type="checkbox"/> PART <input type="checkbox"/> SHEET <input type="checkbox"/> OF |