









REVISIONS				
ZONE	LTR	DESCRIPTION	DATE	APPROVED



NOTE

1. MODEL No : SDP-4055FG
2. OPERATING PRESSURE : 15~250 Kg/cm²)
3. OPERATING TEMPERATURE : 0~60 °C
4. EFFECTIVE AREA(Cm²) : PUSH=12.56 , PULL=6.41
5. PISTON DIAMETER : $\phi 40.0$
6. ROD DIAMETER : $\phi 28.0$

DET.NO		NAME		Q'TY	MAT'L	FINAL SIZES & PART No	REMARK	
UNLESS OTHERWISE SPECIFIED		SIGNATURES		MO-DA-YR		<div><div></div><div>(주)케이제이에프 TOTAL CLAMPING SYSTEMS</div></div> <div>TITLE</div> <div>FLANGE CLAMP</div>		
DIMENSIONS ARE IN MM		DRAWN						
ALL SURFACES 6.3s		CHECKED						
TOLERANCES		APPROVED						
ANGLE X. ± .X ± 0.15 .XX ±								
FINISH		WORK ORDER NO		REF DWG NO.		DWG NO		A2
HEAT TREAT				-		SDx-4045FG_-		
				SCALE		TOOL <input type="checkbox"/> PART <input type="checkbox"/> SHEET		OF

UNLESS OTHERWISE SPECIFIED		SIGNATURES		MO-DA-YR		<div><div></div><div>(주)케이제이에프</div><div>TOTAL CLAMPING SYSTEMS</div></div>			
DIMENSIONS ARE IN MM		DRAWN				TITLE <div>FLANGE CLAMP</div>			
ALL SURFACES 6.3s		CHECKED							
TOLERANCES		APPROVED							
ANGLE X. ± .X ± 0.15 .XX ±									
FINISH		WORK ORDER NO		REF DWG NO.		DWG NO		A2	
HEAT TREAT				SCALE		TOOL <input type="checkbox"/> PART <input type="checkbox"/> SHEET <input type="checkbox"/>		OF	