





REVISIONS				
ZONE	LTR	DESCRIPTION	DATE	APPROVED
△				



Isometric view (1:2)

NOTE

1. MODEL No : SDP-4055GV
2. OPERATING PRESSURE : 15~250 Kg/cm²)
3. OPERATING TEMPERATURE : 0~60 °C
4. EFFECTIVE AREA(Cm²) : PUSH=12.56 , PULL=6.41
5. PISTON DIAMETER : $\phi 40.0$
6. ROD DIAMETER : $\phi 28.0$

DET.NO		NAME		Q'TY	MAT'L	FINAL SIZES & PART No	REMARK
UNLESS OTHERWISE SPECIFIED		SIGNATURES		MO-DA-YR		 (주)케이제이에프 TOTAL CLAMPING SYSTEMS	
DIMENSIONS ARE IN MM		DRAWN		TITLE <h1>FLANGE CLAMP</h1>			
ALL SURFACES 6.3S		CHECKED					
TOLERANCES		APPROVED					
ANGLE ± X. ± .X ± 0.15 .XX ±							
FINISH		WORK ORDER NO		REF DWG NO.	DWG NO		
HEAT TREAT				---	SDP-4055GV_-		
				SCALE	TOOL	PART	SHEET
							OF